

10G Ethernet SFP+ Bidi Family



OPTICAL PARAMETERS

Part number	Fibertype	Wavelength TX [nm]	Wavelength RX [nm]	Opt. Output Power [dBm]	Opt. Receiver Sensitivity [dBm]	Power Budget [dB]	Temp °C
SFP-10G-BX10D-23	SM	1270	1330	-5 to 0	-14 to 0	9	0 to 70
SFP-10G-BX10D-32	SM	1330	1270	-5 to 0	-14 to 0	9	0 to 70
SFP-10G-BX40D-23	SM	1270	1330	-1 to +4	-15 to 0	14	0 to 70
SFP-10G-BX40D-32	SM	1330	1270	-1 to +4	-15 to 0	14	0 to 70
SFP-10G-BX60D-23	SM	1270	1330	0 to 5	-20 to -7	20	0 to 70
SFP-10G-BX60D-32	SM	1330	1270	0 to 5	-20 to -7	20	0 to 70
SFP-10G-BX80D-45	SM	1490	1550	0 to 4	< -23	23	0 to 70
SFP-10G-BX80D-54	SM	1550	1490	0 to 4	< -23	23	0 to 70

ORDERING INFORMATION

Produktnummer	Produktbeskrivelse
SFP-10G-BX10D-23	SFP+ BIDI, 10GE, DDM, SM, 10kmTx/Rx=1270/1330nm, 9dB, LC
SFP-10G-BX10D-32	SFP+ BIDI, 10GE, DDM, SM, 10kmTx/Rx=1330/1270nm, 9dB, LC
SFP-10G-BX40D-23	SFP+ BIDI, 10GE, DDM, SM, 40kmTx/Rx=1270/1330nm, 14dB, LC
SFP-10G-BX40D-32	SFP+ BIDI, 10GE, DDM, SM, 40kmTx/Rx=1330/1270nm, 14dB, LC
SFP-10G-BX60D-23	SFP+ BIDI, 10GE, DDM, SM, 60kmTx/Rx=1270/1330nm, 20dB, LC
SFP-10G-BX60D-32	SFP+ BIDI, 10GE, DDM, SM, 60kmTx/Rx=1330/1270nm, 20dB, LC
SFP-10G-BX80D-45	SFP+ BIDI, 10GE, DDM, SM, 80kmTx/Rx=1490/1550nm, 23dB, LC
SFP-10G-BX80D-54	SFP+ BIDI, 10GE, DDM, SM, 80kmTx/Rx=1550/1490nm, 23dB, LC