

10G Ethernet SFP+ I-Temp Family



OPTICAL PARAMETERS

Part number	Fibertype	Wavelength [nm]	Opt. Output Power [dBm]	Opt. Receiver Sensitivity [dBm]	Power Budget [dB]	Temp °C
SFP-10GE-SR	MM	850	-6 to -1	-10 to 0	4	-40 to 85
SFP-10GE-LRM	MM	1310	-6 to -1	-10 to 0	4	-40 to 85
SFP-10GE-LR	SM	1310	-6 to 1	-15 to 1	9	-40 to 85
SFP-10GE-LR40	SM	1310	-1 to 4	-16 to 0	15	-40 to 85
SFP-10GE-ER	SM	1550	-1 to 4	-16 to 0	15	-40 to 85
SFP-10GE-ZR	SM	1550	0 to 5	-23 to -8	23	-40 to 85

ORDERING INFORMATION

Produktnummer	Produktbeskrivelse
SFP-10G-SR-IND	SFP+, 10GE, DDM, 300m, I-Temp, 850nm, 4dB, MM
SFP-10G-LRM-IND	SFP+, 10GE, DDM, 220m, I-Temp, 1310nm, 3.4dB, MM, requires EDC
SFP-10G-LR-IND	SFP+, 10GE, DDM, 10km, I-Temp, 1310nm, 9dB, SM
SFP-10G-ER-IND	SFP+, 10GE, DDM, 40km, I-Temp, 1550nm, 15dB, SM
SFP-10G-ZR-IND	SFP+, 10GE, DDM, 80km, I-Temp, 1550nm, 23dB, SM