

1G Ethernet SFP Family



OPTICAL PARAMETERS

Part number	Fiber type	Wavelength [nm]	Opt. Output Power [dBm]	Opt. Receiver Sensitivity [dBm]	Power Budget [dB]	Temp °C
SFP-1G-SXD	MM	850	-9 to -3	<-18	9	0 to 70
SFP-1G-LXD	SM/MM	1310	-9 to -3	<-20	10	0 to 70
SFP-1G-L20D	SM	1310	-8 to -3	<-22	14	0 to 70
SFP-1G-L40D	SM	1310	-4 to 8	<-24	20	0 to 70
SFP-1G-ZXD	SM	1550	0 to 5	<-24	24	0 to 70
SFP-1G-L120D	SM	1550	0 to 5	<-32	32	0 to 70
SFP-1G-L160D	SM	1550	0 to 5	<-32	37	0 to 70

ORDERING INFORMATION

Produktnummer	Produktbeskrivelse
SFP-1G-SXD	SFP, 1 GbE, DDM, 550m, 850nm, 9dB, MM
SFP-1G-LXD	SFP, 1 GbE, DDM, 10km, 1310nm, 10dB, SM/MM
SFP-1G-L20D	SFP, 1 GbE, DDM, 20km, 1310nm, 14dB, SM/MM
SFP-1G-L40D	SFP, 1 GbE, DDM, 40km, 1310nm, 20dB, SM/MM
SFP-1G-ZXD	SFP, 1 GbE, DDM, 80km, 1550nm, 24dB, SM/MM
SFP-1G-L120D	SFP, 1 GbE, DDM, 120km, 1550nm, 32dB, SM/MM
SFP-1G-L160D	SFP, 1 GbE, DDM, 160km, 1550nm, 37dB, SM/MM