

1G Ethernet SFP, I-Temp Family



OPTICAL PARAMETERS

Part number	Fibertype	Wavelength [nm]	Opt. Output Power [dBm]	Opt. Receiver Sensitivity [dBm]	Power Budget [dB]	Temp °C
SFP-1G-SX-IND	MM	850	-9 to -3	<-18	9	-40 to 85
SFP-1G-LX-IND	SM/MM	1310	-9 to -3	<-20	10	-40 to 85
SFP-1G-LX-40-IND	SM	1310	-4 to 8	<-24	20	-40 to 85
SFP-1G-ZX-IND	SM	1550	0 to 5	<-24	24	-40 to 85

ORDERING INFORMATION

Produktnummer	Produktbeskrivelse
SFP-1G-SX-IND	SFP, 1 GbE, DDM, 550m, I-Temp, 850nm, 9dB, MM
SFP-1G-LX-IND	SFP, 1 GbE, DDM, 10km, I-Temp, 1310nm, 10dB, SM/MM
SFP-1G-LX-40-IND	SFP, 1 GbE, DDM, 40km, I-Ttemp, 1310nm, 20dB, SM
SFP-1G-ZX-IND	SFP, 1 GbE, DDM, 80km, I-Temp, 1550nm, 24dB, SM