QSFP28 100G CWDM4 2km

QSFP28 transceiver · 100G · 1271 / 1291 / 1311 / 1331 nm (CWDM) · 2 km SMF · Duplex LC · NVIDIA compatible

The GLOBALfiber Q100G-CWDM-4-NV is a 100G QSFP28 transceiver for NVIDIA InfiniBand and Ethernet networks. It uses 4 × 25G NRZ lanes at 1271 / 1291 / 1311 / 1331 nm (CWDM) for links up to 2 km SMF over Duplex LC. The module is coded for NVIDIA equipment and is available with InfiniBand or Ethernet coding.



KEY FEATURES

- QSFP28 form factor
- 100G, 4 × 25G NRZ, 25.78125 Gb/s
- Wavelength 1271 / 1291 / 1311 / 1331 nm (CWDM)
- Reach up to 2 km SMF
- Duplex LC optical connector
- Max. power consumption 3.5 W
- Digital diagnostics (DDM), hot-pluggable
- Case temperature 0 to +70 °C

APPLICATIONS & COMPATIBILITY

- NVIDIA switches: Switch-IB 2 SB7800/SB7890, Quantum QM8700/QM8790 (HDR100/EDR), Spectrum SN2700/SN2100, Spectrum-2 SN3700C, Spectrum-3 SN4600C
- NVIDIA adapters / systems: ConnectX-4, ConnectX-5, ConnectX-6, ConnectX-6 Dx, ConnectX-7, BlueField-2/3
- Replaces NVIDIA MMA1L30-CM

KEY SPECIFICATIONS

Form factor	QSFP28
Data rate	100G
Lanes	4 × 25G NRZ, 25.78125 Gb/s
Wavelength	1271 / 1291 / 1311 / 1331 nm (CWDM)
Reach	2 km SMF
Connector	Duplex LC
Fiber	Singlemode
Max. power	3.5 W
Case temperature	0 to +70 °C
Protocol	InfiniBand or Ethernet (EDR / 100GbE)

ORDERING INFORMATION

GLOBALfiber item	Coding	Replaces NVIDIA	Description
Q100G-CWDM-4-NVI	IB InfiniBand	MMA1L30-CM	QSFP28 100G CWDM4 2km
Q100G-CWDM-4-NVE	ETH Ethernet	MMA1L30-CM	QSFP28 100G CWDM4 2km

Choose the coding that matches the host: InfiniBand for NVIDIA Quantum switches, Ethernet for NVIDIA Spectrum switches. Other coding on request: salg@globalfiber.no.

ABSOLUTE MAXIMUM RATINGS

Parameter	Min	Max	Unit
Supply voltage	-0.5	3.6	V
Control input voltage	-0.3	Vcc+0.5	V
Storage temperature	-40	85	°C
Relative humidity (non-condensing)	5	95	%

RECOMMENDED OPERATING CONDITIONS

Parameter	Min	Typ	Max	Unit
Case temperature	0	–	70	°C
Supply voltage	3.135	3.3	3.465	V
Power consumption	–	–	3.5	W
Link distance	2	–	2000	m

OPTICAL CHARACTERISTICS – TRANSMITTER (PER LANE)

Parameter	Min	Typ	Max	Unit
Lane 0 wavelength	1264.5	1271	1277.5	nm
Lane 1 wavelength	1284.5	1291	1297.5	nm
Lane 2 wavelength	1304.5	1311	1317.5	nm
Lane 3 wavelength	1324.5	1331	1337.5	nm
Side-mode suppression ratio	30	–	–	dB
Total average launch power	–	–	10.5	dBm
Average launch power per lane	-4.3	–	4.5	dBm
OMA per lane	-1.3	–	4.5	dBm
Extinction ratio	4.0	–	–	dB
Average power with TX off	–	–	-30	dBm

OPTICAL CHARACTERISTICS – RECEIVER (PER LANE)

Parameter	Min	Max	Unit
Average receive power per lane	-10.6	4.5	dBm
Receive power OMA	–	4.5	dBm
Sensitivity OMA	–	-8.6	dBm
Stressed sensitivity OMA	–	-6.8	dBm
LOS assert / de-assert	-13.6	-11.6	dBm

DIGITAL DIAGNOSTICS (DDM)

Parameter	Range	Accuracy
Case temperature	0 to 70 °C	±3 °C
Supply voltage	0 to Vcc	±0.1 V
TX bias per lane	0 to 100 mA	±10 %
TX power per lane	Operating range	±3 dB
RX power per lane	Operating range	±3 dB

COMPLIANCE

- 100G CWDM4 MSA
- QSFP28 MSA
- SFF-8636
- Class 1 laser product
- RoHS compliant

INSTALLATION NOTES

- Use in QSFP28 host ports.
- Confirm host support, port mode, firmware version and FEC before deployment.
- Check the optical link budget and fiber loss for the full link (singlemode fiber, Duplex LC).
- Keep connectors clean and capped when not in use.

NVIDIA, Quantum, Spectrum, ConnectX, BlueField and DGX are trademarks of NVIDIA Corporation. GLOBALfiber products are third-party compatible and are not manufactured or endorsed by NVIDIA. Specifications are subject to change without notice.